

EN

EN

EN



EUROPEAN COMMISSION

Brussels, 5.5.2010
COM(2010)225 final

2010/0122 (NLE)

Proposal for a

COUNCIL REGULATION

**amending Council Regulation No 329/2007 concerning restrictive measures against the
Democratic People's Republic of Korea**

EN

(presented jointly by the Commission and the High Representative of the EU for Foreign
Affairs and Security Policy)

EXPLANATORY MEMORANDUM

- (1) Further to UN Security Council resolutions 1718 (2006) and 1874 (2009) Common Position 2006/795/CFSP and Council Regulation (EC) No 329/2007, as amended, make provision for certain restrictive measures against the Democratic People's Republic of Korea (hereinafter 'North Korea').
- (2) In line with Common Position 2006/795/CFSP, Regulation (EC) No 329/2007 in particular restricts the supply, sale or transfer to North Korea of certain items, materials, equipment, goods and technology, in addition to those determined by the UN Security Council or the Sanctions Committee, that could contribute to North Korea's nuclear-related, other weapons of mass destruction-related or ballistic missiles-related programmes. These items are listed in Annex Ia to Regulation (EC) No 329/2007.
- (3) In consideration of North Korea's continuing nuclear proliferation activities, the list of prohibited items in Annex Ia needs to be revised in order to maintain its effectiveness.
- (4) The purpose of this proposal is to update Annex Ia to Council Regulation (EC) No 329/2007, and to empower the Commission to amend the said annex.

Proposal for a

COUNCIL REGULATION

amending Council Regulation (EC) No 329/2007 concerning restrictive measures against the Democratic People's Republic of Korea

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Articles 215(1) thereof,

Having regard to Common Position 2006/795/CFSP concerning restrictive measures against the Democratic People's Republic of Korea¹,

Having regard to the joint proposal from the High Representative of the Union for Foreign Affairs and Security Policy and the Commission,

Whereas:

- (1) In line with Common Position 2006/795/CFSP, Regulation (EC) No 329/2007 in particular restricts the supply, sale, transfer or export to the Democratic People's Republic of Korea (hereinafter referred to as 'North Korea') of certain items, materials, equipment, goods and technology, that could contribute to North Korea's nuclear-related, other weapons of mass destruction-related or ballistic missiles-related programmes, in addition to those determined by the UN Security Council or the Sanctions Committee.
- (2) These items are listed in Annex Ia to Regulation (EC) No 329/2007 and need to be revised in order to maintain their effectiveness.
- (3) For reasons of expediency, the Commission should be empowered to amend the list of prohibited goods and technology, on the basis of information provided by Member States.
- (4) Regulation (EC) No 329/2007 should therefore be amended accordingly,

HAS ADOPTED THIS REGULATION:

Article 1

Regulation (EC) No 329/2007 is amended as follows:

¹ OJ L 322, 22.11.2006, p. 32

(a) Paragraph 1 of Article 13 is replaced by the following:

“1. The Commission shall be empowered to:

- (a) amend Annex Ia on the basis of determinations made by either the Sanctions Committee or the United Nations Security Council or on the basis of information supplied by Member States;
- (b) amend Annex II on the basis of information supplied by Member States;
- (c) amend Annex III in order to refine or adapt the list of goods included therein, according to any definition or guidelines that may be promulgated by the Sanctions Committee or to add the reference numbers taken from the Combined Nomenclature as set out in Annex I to Regulation (EEC) No 2658/87, if necessary or appropriate;
- (d) amend Annex IV on the basis of determinations made by either the Sanctions Committee or the United Nations Security Council; and
- (e) amend Annexes V and VI in accordance with decisions taken concerning Annexes II, III, IV and V of Common Position 2006/795/CFSP.”

(b) Annex Ia to Regulation (EC) No 329/2007 is hereby amended as set out in Annex I to this Regulation.

Article 2

This Regulation shall enter into force on the day following that of its publication in the *Official Journal of the European Union*.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, [...]

For the Council
The President
[...]

ANNEX I

"ANNEX Ia

Goods and technology referred to in Articles 2 and 3

Other items, materials, equipment, goods and technology which could contribute to North Korea's nuclear-related, other weapons of mass destruction-related or ballistic missile-related programmes

1. Unless otherwise stated, reference numbers used in the column entitled "Description" refer to the descriptions of dual use items and technology set out in Annex I to Regulation (EC) No 428/2009.
2. A reference number in the column entitled "Related item from Annex I to Regulation (EC) No 428/2009" means that the characteristics of the item described in the column "Description" lie outside the parameters set out in the description of the dual use entry referred to.
3. Definitions of terms between 'single quotation marks' are given in a technical note to the relevant item.
4. Definitions of terms between "double quotation marks" can be found in Annex I to Regulation (EC) No 428/2009.

General Notes

1. The object of the prohibitions contained in this Annex should not be defeated by the export of any non-prohibited goods (including plant) containing one or more prohibited components when the prohibited component or components are the principal element of the goods and can feasibly be removed or used for other purposes.
N.B.: In judging whether the prohibited component or components are to be considered the principal element, it is necessary to weigh the factors of quantity, value and technological know-how involved and other special circumstances which might establish the prohibited component or components as the principal element of the goods being procured.
2. Goods specified in this Annex include both new and used goods.

General Technology Note (GTN)

(To be read in conjunction with Part C.)

1. The sale, supply, transfer or export of "technology" which is "required" for the "development", "production" or "use" of goods the sale, supply, transfer or export of which is prohibited in Part A (Goods) below, is prohibited in accordance with the provisions of Part .B.

2. The "technology" "required" for the "development", "production" or "use" of prohibited goods remains under prohibition even when applicable to non-prohibited goods.
3. Prohibitions do not apply to that "technology" which is the minimum necessary for the installation, operation, maintenance (checking) and repair of those goods which are not prohibited.
4. Prohibitions on "technology" transfer do not apply to information "in the public domain", to "basic scientific research" or to the minimum necessary information for patent applications.

A. GOODS

NUCLEAR MATERIALS, FACILITIES, AND EQUIPMENT

I.A0. Goods

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A0.001	Hollow cathode lamps as follows: a. Iodine hollow cathode lamps with windows in pure silicon or quartz; b. Uranium hollow cathode lamps.	
I.A0.002	Faraday isolators in the wavelength range 500 nm – 650 nm	
I.A0.003	Optical gratings in the wavelength range 500 nm – 650 nm	
I.A0.004	Optical fibres in the wavelength range 500 nm – 650 nm coated with anti-reflecting layers in the wavelength range 500 nm – 650 nm and having a core diameter greater than 0,4 mm but not exceeding 2 mm.	

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A0.005	<p>Nuclear reactor vessel components and testing equipment, other than those specified in 0A001, as follows:</p> <ul style="list-style-type: none"> a. Seals; b. Internal components; c. Sealing, testing and measurement equipment. 	0A001
I.A0.006	<p>Nuclear detection systems, other than those specified in 0A001.j. or 1A004.c., for detection, identification or quantification of radioactive materials or radiation of nuclear origin and specially designed components thereof.</p> <p><i><u>N.B:</u> For personal equipment refer to I.A1.004 below.</i></p>	0A001.j. 1A004.c.
I.A0.007	Bellows-sealed valves other than those specified in 0B001.c.6., 2A226 or 2B350, made of aluminium alloy or stainless steel type 304, 304L or 316L.	0B001.c.6.2A2 26 2B350

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A0.008	<p>Laser mirrors, other than those specified in 6A005.e., consisting of substrates having a thermal expansion coefficient of 10^{-6} K^{-1} or less at 20 °C (e.g. fused silica or sapphire).</p> <p><i>Note: This item does not cover optical systems specially designed for astronomical applications, except if the mirrors contain fused silica.</i></p>	0B001.g.5. 6A005.e.
I.A0.009	<p>Laser lenses, other than those specified in 6A005.e.2, consisting of substrates having a thermal expansion coefficient of 10^{-6} K^{-1} or less at 20 °C (e.g. fused silica).</p>	0B001.g. 6A005.e.2.
I.A0.010	<p>Pipes, piping, flanges, fittings made of, or lined with nickel, or nickel alloy containing more than 40% nickel by weight, other than those specified in 2B350.h.1.</p>	2B350

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A0.011	<p>Vacuum pumps other than those specified in 0B002.f.2. or 2B231, as follows:</p> <ul style="list-style-type: none"> a. Turbo-molecular pumps having a flow-rate equal to or greater than 400 l/s; b. Roots type vacuum roughing pumps having a volumetric aspiration flow-rate greater than 200 m³/h; c. Bellows-sealed, scroll, dry compressor, and bellows-sealed, scroll, dry vacuum pumps. 	<p>0B002.f.2. 2B231</p>
I.A0.012	<p>Shielded enclosures for the manipulation, storage and handling of radioactive substances (hot cells).</p>	<p>0B006</p>

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A0.013	"Natural uranium" or "depleted uranium" or thorium in the form of metal, alloy, chemical compound or concentrate and any other material containing one or more of the foregoing, other than those specified in 0C001.	0C001
I.A0.014	Detonation chambers having a capacity of explosion absorption of more than 2,5 kg TNT equivalent.	

SPECIAL MATERIALS AND RELATED EQUIPMENT

I.A1. Goods

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A1.001	Bis(2-ethylhexyl) phosphoric acid (HDEHP or D2HPA) Chemical Abstract Number (CAS): [CAS 298-07-7] solvent in any quantity, with a purity greater than 90 %.	
I.A1.002	Fluorine gas CAS: [7782-41-4], with a purity of at least 95 %.	
I.A1.003	Ring-shaped seals and gaskets, having an inner diameter of 400 mm or less, made of any of the following materials: a. Copolymers of vinylidene fluoride having 75% or more beta crystalline structure without stretching; b. Fluorinated polyimides containing 10% by weight or more of combined fluorine; c. Fluorinated phosphazene elastomers containing 30% by weight or more of combined fluorine; d. Polychlorotrifluoroethylene (PCTFE, e.g. Kel-F ®); e. Fluoro-elastomers (e.g., Viton ®, Tecnoflon ®); f. Polytetrafluoroethylene (PTFE).	1A001

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A1.004	Personal equipment for detecting radiation of nuclear origin, other than that specified in 1A004.c., including personal dosimeters.	1A004.c.
I.A1.005	Electrolytic cells for fluorine production, other than those specified in 1B225, with an output capacity greater than 100 g of fluorine per hour.	1B225
I.A1.006	Catalysts, other than those specified in 1A225 or 1B231, containing platinum, palladium or rhodium, usable for promoting the hydrogen isotope exchange reaction between hydrogen and water for the recovery of tritium from heavy water or for the production of heavy water.	1A225 1B231

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A1.007	<p>Aluminium and its alloys, other than those specified in 1C002.b.4. or 1C202.a, in crude or semi-fabricated form having either of the following characteristics:</p> <p>a. 'Capable of' an ultimate tensile strength of 460 MPa or more at 293 K (20 °C); or</p> <p>b. Having a tensile strength of 415 MPa or more at 298 K (25 °C).</p> <p><i><u>Technical note:</u></i></p> <p><i>The phrase alloys 'capable of' encompasses alloys before or after heat treatment.</i></p>	<p>1C002.b.4.</p> <p>1C202.a.</p>

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A1.008	<p>Magnetic metals, of all types and of whatever form, other than those specified in 1C003.a. having an "initial relative permeability" of 120 000 or more and a thickness between 0,05 mm and 0,1 mm.</p> <p><i><u>Technical note:</u></i></p> <p><i>Measurement of "initial relative permeability" must be performed on fully annealed materials.</i></p>	1C003.a.

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A1.009	<p>"Fibrous or filamentary materials" or preregs, other than those specified in 1C010.a., 1C010.b., 1C210.a. or 1C210.b. as follows:</p> <p>a. Aramid "fibrous or filamentary materials" having either of the following characteristics:</p> <ol style="list-style-type: none"> 1. A "specific modulus" exceeding 10×10^6 m; or 2. A "specific tensile strength" exceeding 17×10^4 m; <p>b. Glass "fibrous or filamentary materials" having either of the following characteristics:</p> <ol style="list-style-type: none"> 1. A "specific modulus" exceeding $3,18 \times 10^6$ m; or 2. A "specific tensile strength" exceeding $76,2 \times 10^3$ m; <p>c. Thermoset resin-impregnated continuous "yarns", "rovings", "tows" or "tapes" with a width of 15 mm or less (once preregs), made from glass "fibrous or filamentary materials" other than those specified in I.A1.010.a. below.</p>	<p>1C010.a.</p> <p>1C010.b.</p> <p>1C210.a.</p> <p>1C210.b.</p>

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
	<ul style="list-style-type: none"> d. Carbon "fibrous or filamentary materials"; e. Thermoset resin-impregnated continuous "yarns", "rovings", "tows", or "tapes", made from carbon "fibrous or filamentary materials"; f. Polyacrylonitrile (PAN) continuous "yarns", "rovings", "tows" or "tapes". g. Para-aramid "fibrous or filamentary materials" (Kevlar® and other Kevlar®-like fibres). 	
I.A1.010	<p>Resin-impregnated or pitch-impregnated fibres (prepregs), metal or carbon-coated fibres (preforms) or "carbon fibre preforms", as follows:</p> <ul style="list-style-type: none"> a. Made from "fibrous or filamentary materials" specified in I.A1.009 above; b. Epoxy resin "matrix" impregnated carbon "fibrous or filamentary materials" (prepregs), specified in 1C010.a., 1C010.b. or 1C010.c., for the repair of aircraft structures or laminates, of which the size of individual sheets does not exceed 50 cm × 90 cm; c. Prepregs specified in 1C010.a., 1C010.b. or 1C010.c., when impregnated with phenolic or epoxy resins having a glass transition temperature (T_g) less than 433 K (160 °C) and a cure temperature lower than the glass transition temperature. 	<p>1C010 1C210</p>

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A1.011	Reinforced silicon carbide ceramic composites usable for nose tips, re-entry vehicles, nozzle flaps, usable in "missiles", other than those specified in 1C107.	1C107
I.A1.012	Not used	
I.A1.013	<p>Tantalum, tantalum carbide, tungsten, tungsten carbide and alloys thereof, other than those specified in 1C226, having both of the following characteristics:</p> <ul style="list-style-type: none"> a. In forms having a hollow cylindrical or spherical symmetry (including cylinder segments) with an inside diameter between 50 mm and 300 mm; <u>and</u> b. A mass greater than 5 kg. 	1C226

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A1.014	<p>"Elemental powders" of cobalt, neodymium or samarium or alloys or mixtures thereof containing at least 20% by weight of cobalt, neodymium or samarium, with a particle size less than 200 µm.</p> <p><i>Technical note:</i></p> <p><i>"Elemental powder" means a high purity powder of one element.</i></p>	
I.A1.015	<p>Pure tributyl phosphate (TBP) [CAS No 126-73-8] or any mixture having a TBP content of more than 5% by weight.</p>	
I.A1.016	<p>Maraging steel, other than those specified by 1C116 or 1C216.</p> <p><i>Technical notes:</i></p> <p><i>1. The phrase maraging steel "capable of" encompasses maraging steel before or after heat treatment.</i></p> <p><i>2. Maraging steels are iron alloys generally characterised by high nickel, very low carbon content and the use of substitutional elements or precipitates to produce strengthening and age-hardening of the alloy.</i></p>	<p>1C116</p> <p>1C216</p>
I.A1.017	<p>Metals, metal powders and material as follows:</p> <p>a. Tungsten and tungsten alloys, other than those specified in 1C117, in the form of uniform spherical or atomized particles of 500 µm (micrometre) diameter or less with a tungsten content of 97% by weight or more;</p> <p>b. Molybdenum and molybdenum alloys, other than those specified in 1C117, in the form of uniform spherical or atomized particles of 500 µm diameter or less with a molybdenum content of 97% by weight or more;</p> <p>c. Tungsten materials in the solid form, other than those specified in 1C226 having material compositions as follows:</p>	<p>1C117</p> <p>1C226</p>

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
	<ol style="list-style-type: none"> 1. Tungsten and alloys containing 97% by weight or more of tungsten; 2. Copper infiltrated tungsten containing 80% by weight or more of tungsten; or 3. Silver infiltrated tungsten containing 80% by weight or more of tungsten. 	

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A1.018	Soft magnetic alloys, other than those specified in 1C003, having a chemical composition as follows: a Iron content between 30% and 60%; and b Cobalt content between 40% and 60%.	1C003
I.A1.019	Not used	
I.A1.020	Graphite, other than that specified in 0C004 or 1C107.a, designed or specified for use in Electrical Discharge Machining (EDM) machines	0C004 1C107a

MATERIALS PROCESSING

I.A2. Goods

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A2.001	<p>Vibration test systems, equipment and components thereof, other than those specified in 2B116:</p> <p>a. Vibration test systems employing feedback or closed loop techniques and incorporating a digital controller, capable of vibrating a system at an acceleration equal to or greater than 0,1 g rms between 0,1 Hz and 2 kHz and imparting forces equal to or greater than 50 kN, measured 'bare table';</p> <p>b. Digital controllers, combined with specially designed vibration test "software", with a "real-time control bandwidth" greater than 5 kHz designed for use with vibration test systems specified in a.;</p> <p><i>Technical note:</i> <i>'Real-time control bandwidth' is defined as the maximum rate at which a controller can execute complete cycles of sampling, processing data and transmitting control signals.</i></p>	2B116
	<p>c. Vibration thrusters (shaker units), with or without associated amplifiers, capable of imparting a force equal to or greater than 50 kN, measured 'bare table', and usable in vibration test systems specified in a.;</p> <p>d. Test piece support structures and electronic units designed to combine multiple shaker units in a system capable of providing an effective combined force equal to or greater than 50 kN, measured 'bare table', and usable in vibration systems specified in a.</p> <p><i>Technical note:</i> <i>'bare table' means a flat table, or surface, with no fixture or fittings.</i></p>	

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A2.002	<p>Machine tools, other than those specified in 2B001.c. or 2B201.b., for grinding having positioning accuracies with "all compensations available" equal to or less (better) than 15 µm according to ISO 230/2 (1988)¹ or national equivalents along any linear axis.</p> <p>¹ Manufacturers calculating positioning accuracy in accordance with ISO 230/2 (1997) should consult the competent authorities of the Member State in which they are established.</p>	<p>2B001.c. 2B201.b.</p>

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A2.002a	Components and numerical controls, specially designed for machine tools specified in 2B001, 2B201, or I.A2.002 above.	
I.A2.003	<p>Balancing machines and related equipment as follows:</p> <ol style="list-style-type: none"> a. Balancing machines, designed or modified for dental or other medical equipment, having all the following characteristics: <ol style="list-style-type: none"> 1. Not capable of balancing rotors/assemblies having a mass greater than 3 kg; 2. Capable of balancing rotors/assemblies at speeds greater than 12 500 rpm; 3. Capable of correcting unbalance in two planes or more; <u>and</u> 4. Capable of balancing to a residual specific unbalance of 0,2 g x mm per kg of rotor mass; b. 'Indicator heads' designed or modified for use with machines specified in a. above. <p><i>Technical note:</i></p> <p><i>'Indicator heads' are sometimes known as balancing instrumentation.</i></p>	2B119

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A2.004	<p>Remote manipulators that can be used to provide remote actions in radiochemical separation operations or hot cells, other than those specified in 2B225, having either of the following characteristics:</p> <ul style="list-style-type: none"> a. A capability of penetrating a hot cell wall of 0,3 m or more (through the wall operation); or b. A capability of bridging over the top of a hot cell wall with a thickness of 0,3 m or more (over the wall operation). <p><i>Technical note:</i></p> <p><i>Remote manipulators provide translation of human operator actions to a remote operating arm and terminal fixture. They may be of master/slave type or operated by joystick or keypad.</i></p>	2B225
I.A2.005	<p>Controlled atmosphere heat treatment furnaces or oxidation furnaces capable of operation at temperatures above 400 °C</p> <p><i>Note: This item does not cover tunnel kilns with roller or car conveyance, tunnel kilns with conveyor belt, pusher type kilns or shuttle kilns, specially designed for the production of glass, tableware ceramics or structural ceramics.</i></p>	2B226 2B227

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A2.006	Not used	
I.A2.007	<p>"Pressure transducers", other than those defined in 2B230, capable of measuring absolute pressures at any point in the range 0 to 200 kPa and having both of the following characteristics:</p> <ol style="list-style-type: none"> a. Pressure sensing elements made of or protected by "Materials resistant to corrosion by uranium hexafluoride (UF₆)", and b. Having either of the following characteristics: <ol style="list-style-type: none"> 1. A full scale of less than 200 kPa and an 'accuracy' of better than ± 1 % of full scale; or 2. A full scale of 200 kPa or greater and an 'accuracy' of better than 2 kPa. <p><i>Technical note:</i></p> <p><i>For the purposes of 2B230, 'accuracy' includes non-linearity, hysteresis and repeatability at ambient temperature.</i></p>	2B230
I.A2.008	<p>Liquid-liquid contacting equipment (mixer-settlers, pulsed columns, plate columns, centrifugal contactors); and liquid distributors, vapour distributors or liquid collectors designed for such equipment, where all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:</p> <ol style="list-style-type: none"> a. Alloys with more than 25 % nickel and 20 % chromium by weight; b. Fluoropolymers; c. Glass (including vitrified or enamelled coating or glass lining); d. Graphite or 'carbon graphite'; e. Nickel or alloys with more than 40 % nickel by weight; f. Tantalum or tantalum alloys; g. Titanium or titanium alloys; h. Zirconium or zirconium alloys; or i. Stainless steel. <p><i>Technical note:</i></p> <p><i>'Carbon graphite' is a composition consisting of amorphous carbon</i></p>	2B350.e

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
	<i>and graphite, in which the graphite content is 8 % or more by weight.</i>	

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A2.009	<p>Industrial equipment and components, other than those specified in 2B350.d., as follows:</p> <p>Heat exchangers or condensers with a heat transfer surface area greater than 0,05 m², and less than 30 m²; and tubes, plates, coils or blocks (cores) designed for such heat exchangers or condensers, where all surfaces that come in direct contact with the fluid(s) are made from any of the following materials:</p> <ul style="list-style-type: none"> a. Alloys with more than 25% nickel and 20% chromium by weight; b. Fluoropolymers; c. Glass (including vitrified or enamelled coating or glass lining); d. Graphite or 'carbon graphite'; 	2B350.d.

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
	<p>e. Nickel or alloys with more than 40% nickel by weight;</p> <p>f. Tantalum or tantalum alloys;</p> <p>g. Titanium or titanium alloys;</p> <p>h. Zirconium or zirconium alloys;</p> <p>i. Silicon carbide;</p> <p>j. Titanium carbide; or</p> <p>k. Stainless steel.</p> <p><i>Note: This item does not cover vehicle radiators.</i></p> <p><i>Technical note:</i></p> <p><i>The materials used for gaskets and seals and other implementation of sealing functions do not determine the status of control of the heat exchanger.</i></p>	

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A2.010	<p>Multiple-seal, and seal-less pumps, other than those specified in 2B350.i, suitable for corrosive fluids, or vacuum pumps and casings (pump bodies), preformed casing liners, impellers, rotors or jet pump nozzles designed for such pumps, in which all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:</p> <p>a. Alloys with more than 25 % nickel and 20 % chromium by weight;</p> <p>b. Ceramics;</p> <p>c. Ferrosilicon;</p> <p>d. Fluoropolymers;</p> <p>e. Glass (including vitrified or enamelled coatings or glass lining);</p> <p>f. Graphite or 'carbon graphite';</p> <p>g. Nickel or alloys with more than 40% nickel by weight;</p> <p>h. Tantalum or tantalum alloys;</p> <p>i. Titanium or titanium alloys;</p> <p>j. Zirconium or zirconium alloys;</p> <p>k. Niobium (columbium) or niobium alloys;</p> <p>l. Stainless steel;</p> <p>m. Aluminium alloys;</p> <p>n. Rubber.</p> <p><u>Technical notes:</u></p> <p>1. <i>The materials used for gaskets and seals and other implementation of sealing functions do not determine the status of control of the pump.</i></p> <p>2. <i>The term “rubber” encompasses all kinds of natural and synthetic rubbers.</i></p>	2B350.i

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A2.011	<p>"Centrifugal separators", other than those specified in 2B352.c., capable of continuous separation without the propagation of aerosols and manufactured from:</p> <ul style="list-style-type: none"> a. Alloys with more than 25 % nickel and 20 % chromium by weight; b. Fluoropolymers; c. Glass (including vitrified or enamelled coating or glass lining); d. Nickel or alloys with more than 40 % nickel by weight; e. Tantalum or tantalum alloys; f. Titanium or titanium alloys; <u>or</u> g. Zirconium or zirconium alloys. <p><i>Technical note:</i></p> <p><i>'Centrifugal separators' include decanters.</i></p>	2B352.c.

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A2.012	Sintered metal filters, other than those specified in 2B352.d., made of nickel or nickel alloy with more than 40 % nickel by weight.	2B352.d.
I.A2.013	<p>Spin-forming machines and flow-forming machines, other than those specified by 2B009, 2B109 or 2B209 and specially designed components therefor.</p> <p><i>Technical note:</i></p> <p><i>For the purpose of this item, machines combining the functions of spin-forming and flow-forming are regarded as flow-forming machines.</i></p>	<p>2B009</p> <p>2B109</p> <p>2B209</p>
I.A2.014	<p>Equipment and reagents, other than those specified in 2B350 or 2B352, as follows:</p> <p>a. fermenters capable of cultivation of pathogenic "micro-organisms" or viruses, or capable of toxin production, without the propagation of aerosols, and having a total capacity of 10 l or more;</p> <p>b. agitators for fermenters as mentioned in the paragraph above;</p> <p><i>Technical Note:</i></p> <p><i>Fermenters include bioreactors, chemostats and continuous-flow systems.</i></p> <p>c. laboratory equipment as follows:</p> <ol style="list-style-type: none"> 1. polymerase chain reaction (PCR)-equipment, 2. genetic sequencing equipment, 3. genetic synthesizers, 4. electroporation equipment, 5. specific reagents associated with the equipment 	<p>2B350,</p> <p>2B352</p>

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
	<p style="text-align: center;">in I.A2.014.c1 – 4 above;</p> <p>d. filters, micro-filters, nano-filters or ultra-filters usable in industrial or laboratory biology for continuous filtering, except filters specially designed or modified for medical or clear water production purposes and to be used in the framework of EU or UN officially supported projects;</p> <p>e. ultracentrifuges, rotors and adaptors for ultracentrifuges;</p> <p>f. freeze drying equipment.</p>	
I.A2.015	<p>Equipment, other than that specified in 2B005, 2B105 or 3B001.d, for the deposition of metallic overlays as follows, and specially designed components and accessories therefor:</p> <p>a. chemical vapour deposition (CVD) production equipment;</p> <p>b. physical vapour deposition (PVD) production equipment;</p> <p>c. production equipment for deposition by means of inductive or resistance heating.</p>	2B005, 2B105, 3B001.d
I.A2.016	<p>Open tanks or containers, with or without agitators, with a total internal (geometric) volume greater than 0.5 m³ (500 litres), where all surfaces that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials:</p> <p>a. Alloys with more than 25 % nickel and 20 % chromium by weight;</p> <p>b. Fluoropolymers;</p> <p>c. Glass (including vitrified or enamelled coatings or glass lining);</p> <p>d. Nickel or alloys with more than 40% nickel by weight;</p> <p>e. Tantalum or tantalum alloys;</p> <p>f. Titanium or titanium alloys;</p> <p>g. Zirconium or zirconium alloys;</p> <p>h. Niobium (columbium) or niobium alloys;</p> <p>i. Stainless steel;</p> <p>g. Wood;</p> <p>k. Rubber.</p>	2B350

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
	<p><i><u>Technical note:</u></i></p> <p><i>The term “rubber” encompasses all kinds of natural and synthetic rubbers.</i></p>	

ELECTRONICS

I.A3. Goods

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A3.001	<p>High voltage direct current power supplies, other than those specified in 0B001.j.5. or 3A227, having both of the following characteristics:</p> <p>a. Capable of continuously producing, over a time period of eight hours, 10 kV or more, with output power of 5 kW or more with or without sweeping; and</p> <p>b. Current or voltage stability better than 0,1 % over a time period of four hours.</p>	0B001.j.5. 3A227
I.A3.002	<p>Mass spectrometers, other than those specified in 0B002.g or 3A233 , capable of measuring ions of 200 atomic mass units or more and having a resolution of better than 2 parts in 200, as follows, and ion sources therefor:</p> <p>a. Inductively coupled plasma mass spectrometers (ICP/MS);</p> <p>b. Glow discharge mass spectrometers (GDMS);</p> <p>c. Thermal ionisation mass spectrometers (TIMS);</p>	0B002.g 3A233

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
	<p>d. Electron bombardment mass spectrometers which have a source chamber constructed from, lined with or plated with "materials resistant to corrosion by uranium hexafluoride UF₆";</p> <p>e. Molecular beam mass spectrometers having either of the following characteristics:</p> <ol style="list-style-type: none"> 1. A source chamber constructed from, lined with or plated with stainless steel or molybdenum and equipped with a cold trap capable of cooling to 193 K (-80°C) or less; <u>or</u> 2. A source chamber constructed from, lined with or plated with materials resistant to UF₆; <p>f. Mass spectrometers equipped with a micro-fluorination ion source designed for actinides or actinide fluorides.</p>	

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A3.003	<p>Frequency changers or generators, other than those specified by 0B001.b.13 or 3A225, having all of the following characteristics, and specially designed components and software therefor:</p> <ul style="list-style-type: none"> a. Multiphase output capable of providing a power of 40 W or greater; b. Capable of operating in the frequency range between 600 and 2 000 Hz; and c. Frequency control better (less) than 0,1%. <p><i>Technical notes:</i></p> <ol style="list-style-type: none"> 1. <i>Frequency changers are also known as converters, inverters, generators, electronic test equipment, AC power supplies, variable speed motor drives or variable frequency drives.</i> 2. <i>The functionality specified in this item may be met by certain equipment marketed as; electronic test equipment, AC power supplies, variable speed motor drives or variable frequency drives.</i> 	0B001.b.13. 3A225

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A3.004	Spectrometers and diffractometers, designed for the indicative test or quantitative analysis of the elemental composition of metals or alloys without chemical decomposition of the material.	

SENSORS AND LASERS

I.A6. Goods

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A6.001	Yttrium aluminium garnet (YAG) rods.	
I.A6.002	Optical equipment and components, other than those specified in 6A002 or 6A004.b as follows: Infrared optics in the wavelength range 9 μm – 17 μm and components thereof, including cadmium telluride (CdTe) components.	6A002 6A004.b.
I.A6.003	Wave front corrector systems, other than mirrors specified in 6A004.a, 6A005.e or 6A005.f., for use with a laser beam having a diameter exceeding 4 mm, and specially designed components thereof, including control systems, phase front sensors and "deformable mirrors" including bimorph mirrors.	6A004.a. 6A005.e. 6A005.f.

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A6.004	Argon ion "lasers", other than those specified in 0B001.g.5, 6A005 and or 6A205.a., having an average output power equal to or greater than 5 W.	0B001.g.5. 6A005.a.6. 6A205.a.
I.A6.005	<p>Semiconductor "lasers", other than those specified in 0B001.g.5., 0B001.h.6. or 6A005.b., and components thereof, as follows:</p> <p>a. Individual semiconductor "lasers" with an output power greater than 200 mW each, in quantities larger than 100;</p> <p>b. Semiconductor "laser" arrays having an output power greater than 20 W.</p> <p><i>Notes:</i></p> <p>1. Semiconductor "lasers" are commonly called "laser" diodes.</p> <p>2. This item does not cover "laser" diodes with a wavelength in the range 1,2 μm – 2,0 μm.</p>	0B001.g.5. 0B001.h.6. 6A005.b.

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A6.006	<p>Tunable semiconductor "lasers" and tunable semiconductor "laser" arrays, other than those specified in 0B001.h.6. or 6A005.b., of a wavelength between 9 μm and 17 μm, as well as array stacks of semiconductor "lasers" containing at least one tunable semiconductor "laser" array of such wavelength.</p> <p><i>Note:</i> Semiconductor "lasers" are commonly called "laser" diodes.</p>	0B001.h.6. 6A005.b.
I.A6.007	<p>Solid state "tunable" "lasers", other than those specified in 0B001.g.5., 0B001.h.6. or 6A005.c.1., and specially designed components thereof as follows:</p> <ul style="list-style-type: none"> a. Titanium-sapphire lasers, b. Alexandrite lasers. 	0B001.g.5. 0B001.h.6. 6A005.c.1.

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A6.008	Neodymium-doped (other than glass) "lasers", other than those specified in 6A005.c.2.b., having an output wavelength greater than 1,0 μm but not exceeding 1,1 μm and output energy exceeding 10 J per pulse.	6A005.c.2.b.
I.A6.009	<p>Components of acousto-optics, as follows:</p> <ul style="list-style-type: none"> a. Framing tubes and solid-state imaging devices having a recurrence frequency equal to or exceeding 1 kHz; b. Recurrence frequency supplies; c. Pockels cells. 	6A203.b.4.

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A6.010	<p>Radiation-hardened cameras, or lenses thereof, other than those specified in 6A203.c., specially designed, or rated as radiation-hardened, to withstand a total radiation dose greater than 50×10^3 Gy(silicon) (5×10^6 rad (silicon)) without operational degradation.</p> <p><i>Technical note:</i> <i>The term Gy(silicon) refers to the energy in Joules per kilogram absorbed by an unshielded silicon sample when exposed to ionising radiation.</i></p>	6A203.c.

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A6.011	<p>Tunable pulsed dye laser amplifiers and oscillators, other than those specified in 0B001.g.5, 6A005 and or 6A205.c., having all of the following characteristics:</p> <ul style="list-style-type: none"> a. Operating at wavelengths between 300 nm and 800 nm; b. An average output power greater than 10 W but not exceeding 30 W; c. A repetition rate greater than 1 kHz; and d. Pulse width less than 100 ns. <p><i>Note:</i> <i>This item does not cover single mode oscillators.</i></p>	0B001.g.5. 6A005 6A205.c.

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A6.012	<p>Pulsed carbon dioxide "lasers", other than those specified in, 0B001.h.6., 6A005.d. or 6A205.d., having all of the following characteristics:</p> <ul style="list-style-type: none"> a. Operating at wavelengths between 9µm and 11µm; b. A repetition rate greater than 250 Hz; c. An average output power greater than 100 W but not exceeding 500 W; and d. Pulse width less than 200 ns. 	<p>0B001.h.6. 6A005.d. 6A205.d.</p>

NAVIGATION AND AVIONICS

I.A7. Goods

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A7.001	<p>Inertial navigation systems and specially designed components thereof, as follows:</p> <p>a. Inertial navigation systems which are certified for use on "civil aircraft" by civil authorities of a State participating in the Wassenaar Arrangement, and specially designed components thereof, as follows:</p> <p>1. Inertial navigation systems (INS) (gimballed or strapdown) and inertial equipment designed for "aircraft", land vehicle, vessels (surface or underwater) or "spacecraft" for attitude, guidance or control, having any of the following characteristics, and specially designed components thereof:</p> <p>a. Navigation error (free inertial) subsequent to normal alignment of 0,8 nautical mile per hour (nm/hr) 'Circular Error Probable' (CEP) or less (better); or</p> <p>b. Specified to function at linear acceleration levels exceeding 10 g;</p>	<p>7A001</p> <p>7A003</p> <p>7A101</p> <p>7A103</p>

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
	<ol style="list-style-type: none"> 2. Hybrid Inertial Navigation Systems embedded with Global Navigation Satellite Systems(s) (GNSS) or with "Data-Based Referenced Navigation" ("DBRN") System(s) for attitude, guidance or control, subsequent to normal alignment, having an INS navigation position accuracy, after loss of GNSS or "DBRN" for a period of up to four minutes, of less (better) than 10 metres 'Circular Error Probable' (CEP); 3. Inertial Equipment for Azimuth, Heading, or North Pointing having any of the following characteristics, and specially designed components thereof: <ol style="list-style-type: none"> a. Designed to have an Azimuth, Heading, or North Pointing accuracy equal to, or less (better) than 6 arc minutes RMS at 45 degrees latitude; or b. Designed to have a non-operating shock level of at least 900 g at a duration of at least 1 msec. 	

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
	<p>b. Theodolite systems incorporating inertial equipment specially designed for civil surveying purposes and designed to have an Azimuth, Heading, or North Pointing accuracy equal to, or less (better) than 6 arc minutes RMS at 45 degrees latitude, and specially designed components thereof.</p> <p>c. Inertial or other equipment using accelerometers specified in 7A001 or 7A101, where such accelerometers are specially designed and developed as MWD (Measurement While Drilling) sensors for use in down-hole well services operations.</p> <p><i>Note: The parameters of a.1. and a.2. are applicable with any of the following environmental conditions:</i></p> <p>1. <i>Input random vibration with an overall magnitude of 7,7 g rms in the first half hour and a total test duration of one and a half hours per axis in each of the three perpendicular axes, when the random vibration meets the following:</i></p> <p>a. <i>A constant power spectral density (PSD) value of 0,04 g²/Hz over a frequency interval of 15 to 1 000 Hz; and</i></p>	

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
	<p><i>b. The PSD attenuates with a frequency from 0,04 g²/Hz to 0,01 g²/Hz over a frequency interval from 1 000 to 2 000 Hz;</i></p> <p><i>2. A roll and yaw rate equal to or greater than +2,62 radian/s (150 deg/s); or</i></p> <p><i>3. According to national standards equivalent to 1. or 2. above.</i></p> <p><u><i>Technical notes:</i></u></p> <p><i>1. a.2. refers to systems in which an INS and other independent navigation aids are built into a single unit (embedded) in order to achieve improved performance.</i></p> <p><i>2. 'Circular Error Probable' (CEP) – In a circular normal distribution, the radius of the circle containing 50 percent of the individual measurements being made, or the radius of the circle within which there is a 50 percent probability of being located.</i></p>	

AEROSPACE AND PROPULSION

I.A9. Goods

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.A9.001	Explosive bolts.	
I.A9.002	Internal combustion engines (i.e. axial piston or rotary piston type), designed or modified for propelling “aircrafts” or “lighter-than-air-vehicles” and specially designed components therefore.	-
I.A9.003	Trucks, other than those specified in 9A115, having more than one motorised axle and a payload exceeding 5 tonnes. <i>Note:</i> <i>This item includes flatbed trailers, semi trailers and other trailers.</i>	9A115

B. SOFTWARE

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.B.001	Software required for the development, production or use of the items in Part A. (Goods).	

C. TECHNOLOGY

No	Description	Related item from Annex I to Regulation (EC) No 428/2009
I.C.001	Technology required for the development, production or use of the items in Part A. (Goods).	